

SP-1310AS-H/PB



自动缝皮牌专用机

Automatic Label Attaching Machine

适用于箱包、服装等皮牌或标牌的缝纫。缝纫范围是130×100mm;特殊设计的缝制平台可作为缝制物料提供适合的缝纫位置,操作简便灵活。

It is suitable for sewing leather tags or signs for luggage and clothes. The sewing range is 130×100mm. The sewing platform is specially designed, which can provide suitable sewing location for various sewing materials, with simple and flexible operations.

规格

- 线迹单针平缝
- 最高缝纫速度2,700rpm
- 最大缝制区域130×100mm
- 大压脚高度一体式压脚
- 马达AC伺服马达550W直接驱动式
- 电源: 单相100~120V、200~240V、三相200~240V、380~415V、350V
- 气压0.5Mpa、1.8L/min

Specification

- Single-needle flatseam
- Highest sewing speed 2,700rpm
- Sewing area 130×100mm
- Big work clamp height All-in-one presserfoot
- Motor AC servomotor 550W
- Power Singlephase 100~120V、200~240V、3-phase 200~240V、380~415V、350V
- Airpressure 0.5Mpa、1.8L/min

高效率高品质

传统平车加工皮牌,约每小时加工60个,舒普自动缝皮牌专用机4秒加工一个皮牌,每小时可加工900个,生产效率提升15倍。

High efficiency and high quality

Traditional plain sewing of leather tags has output of 60 tags per hour. However, SUPREME automatic leather tag attaching machine can process a leather tag every 4 seconds, 900 tags every hour, which improves productivity by 15 times.



SP-2210DH-ASN(单针)/ADN(双针)



自动缝袋花专用机

Automatic Pocket Pattern Sewing Machine

主要适用于工作装、牛仔装、休闲装等口袋装饰线迹的缝纫,机头搭载的电子花样机除了可以胜任普通的平缝线迹以外,还可以同时缝纫各类套结及装饰线迹,缝纫范围为220mm×100mm,可适用于各类的口袋装饰线迹缝纫。


The machine is mainly used for pocket decorative stitch sewing for work wear, jeans and casual wear. The pattern tacker machine head can sew all kinds of tackings and decorative stitches in addition to common flat sewing stitches. The range of sewing is 220mm×100mm, which can be used to sew all kinds of pocket decorative stitches.

实例分析

- 自动化生产工艺
- 送料、车缝、收料一次性完成
- 普通工艺需要2人加工完成,线迹不精准,效率低。采用双针杆袋花样机无需划线,自动送料、车缝、收料一次性完成,线迹美观,可同时车缝两种不同颜色的面线,并且1人可同时操作三台设备。
- 10小时产量2000条裤子/人

Cases

- Automatic production
- Feeding, sewing and collecting in one process
- Traditional process requires 2 workers to operate, but stitching is inaccurate and laborious. With double needle pattern sewing machine, one worker can operate 3 machines in one time while sews double color. It integrated feeding, sewing and collecting into one process and sews beautiful stitching lines.
- 10 hours productivity 2000 pants/person



规格

- 线迹单针平缝
- 最高缝纫速度2,700rpm
- 缝制区域最大220×100mm
- 压脚驱动方式 气动
- 间歇压上升量22mm
- 间歇压上行程0或2-10mm (出厂设置: 3mm)
- 用户程序数50
- 循环程序数9
- 马达AC伺服马达550W直接驱动式
- 电源单相
- 气压0.5Mpa、1.8L/min

Specification

- Single-needle flatseam
- Highest sewing speed 2,700rpm
- Sewing area 220×100mm
- Presser foot moved by Pneumatic
- Raising amount by intermittent presserfoot 22mm
- Stroke by intermittent presser foot 0 or 2-10mm (Factory defaults: 3mm)
- Customer programme amount 50
- Recycle program amount 9
- Motor Direct Drive AC servo motor 550W
- Power Singlephase 200~240V
- Airpressure 0.5Mpa、1.8L/min

